

# **EC-TYPE EXAMINATION CERTIFICATE**



The following model of Personal Protective Equipment has been subjected to an EC-type examination in accordance with the article 10 of the PPE. Directive (89/686/EEC) and has been shown to satisfy the relevant provisions of the Directive.

Certificate N° 0075/1855/162/09/16/1043

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment:

Manufacturer: SHANDONG XINRUIDA LABOR PROTECTIVE PRODUCTS CO., LTD

NORTH OF WEIJIAO ROAD, EAST OF KANGCHENG STREET, ECONOMIC DEVELOPMENT ZONE, GAOMI CITY, SHANDONG

**CHINA** 

Distributor:

**Description** 

PPE Type: protective glove against mechanical risks

Product reference: PU134102P

Glove description: 13G Black Polyester Shell, Black PU Coating Glove

This product is a category II.

Available sizes: 6/XS 7/S 8/M 9/L 10/XL 11/XXL

**Pictures:** 



ITEM NO.: PU134102P EN388

SIZE 10/>

Levels of performance / class of protection

EN 420:2003+A1:2009

EN 388:2016

4131X

The levels of performance have been measured on the palm

« X » means that the test hasn't been performed; no protection is required

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EC-type examination and information given on the product are detailed in the manufacturer's technical file index 02 dated from FEBRUARY, 2018

NOTA: Any modification to new items of the personal protective equipment object of this CE type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the CE type approval certificate (change of adress, change of company status) should be brought to the attention of the notified body in accordance with law n° R.4313-38 of the French Code of Work

Issued in Lyon by

Lionel Gaudillere
PPE certification manage

**Date of issue :** September 15th, 2016 **Update 01 on** February 28th, 2018



cemarking@ctcgroupe.com

CTC - 4, rise Hermann Frenkel - 69367 Lyon cedex 07 - France Tel.: +33 (0)4 72 76 10 10 - Fax: +33 (0)4 72 76 10 00 - ctd/yan@ctcgroupe.com



In application of the Directive 89/686/EEC of the 21th December 1989, concerning the alignment of member states legislation relating to personal protective equipment and in application of relevant requirements of the french labor code, providing by the transcription of these Directive into french regulation.

# SHANDONG XINRUIDA LABOR PROTECTIVE PRODUCTS CO., LTD

# **MANUFACTURER'S TECHNICAL FILE**

Reference of the product : PU134102P

Technical file index : 02

Last update : FEBRUARY, 2018

# **IDENTIFICATION**

Reference of the product :

PU134102P

Basic model

Technical file index:

02

Last update:

FEBRUARY, 2018

#### Manufacturer:

SHANDONG XINRUIDA LABOR PROTECTIVE PRODUCTS CO., LTD NORTH OF WEIJIAO ROAD, EAST OF KANGCHENG STREET, ECONOMIC DEVELOPMENT ZONE, GAOMI CITY, SHANDONG

#### **CHINA**

tel: +86-536-2580591 fax: +86-536-2580591

#### Factory:

SHANDONG XINRUIDA LABOR PROTECTIVE PRODUCTS CO., LTD NORTH OF WEIJIAO ROAD, EAST OF KANGCHENG STREET, ECONOMIC DEVELOPMENT ZONE, GAOMI CITY, SHANDONG

#### **CHINA**

tel: +86-536-2580591 +86-536-2580591 fax:

# **GLOVE DESCRIPTION**

# Glove description:

13G Black Polyester Shell, Black PU Coating Glove

type of coating finish: smooth

# Visual description:



# Field of use, Risks against which the product protects:

Mechanical risk

# **Available sizes:**

Minimum length of glove (mm)	Sizes
220	6/XS
230	7/S
240	8/M
250	9/L
260	10/XL
270	11/XXL

# **Glove constitution:**

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm		black	PU	92g/m²		1mm
		black	polyester	156g/m²	13	
Back		black	polyester	156g/m²	13	
Cuff		black	polyester+elastic	296g/m²	13	
Binding		black	polyester			

# **PROTECTION SCOPE**

This glove meets the essential requirements of the Personal Protection Equipment Directive (89/686/CE).

This glove is designed for mechanical risks.

It is a category II product.

#### **GENERAL REQUIREMENTS**

# Standard EN 420 : 2003 + A1 : 2009

Dexterity:

5

PH of glove and lining is greater than 3.5 and lower than 9.5:

yes

Chromium VI lower than the detection limit:

conform

Size: conform

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

# SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

#### Mechanical hazard EN 388: 2016

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	1
Tear strength resistance	3
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	X
Impact Protection	20

The levels of performance have been measured on the palm « X » means that the test hasn't been performed; no protection is required

# **TEST REPORTS**

Laboratory	стс	Other
EN 420	SH62009-13 SH62502-13 SH60927-13	
Azo	SH62009-13 SH60927-13	16;
EN 388	SH62009-13 S180201510_1	
OTHER	SH62009-13(TIN,CAD) S160707233_2(PAHS) S180100113_1(DMFU)	

# **MARKING - PACKAGING**

#### Information printed on the glove:

Logo of the authorized representative :

Logo (€

Glove's reference: PU134102P

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

### Marking example:



# Method of marking on the glove:

PRINT LOGO ON THE BACK OF GLOVES

#### Packaging:

ONE PAIR ONE INDIVIDUAL POLYBAG OR 12 PAIRS/POLYBAG, THEN 10 OR 20 DOZEN IN THE CARTON.

# **MEANS OF CONTROL**

First is the incoming quality control, which is very important in purchasing the yarn. This is the primary control point to stop the defective materials into the productive process. Through some physical methods, such as visual, touch, compare with the samples, the best quality of yarns will be choosed for gloves.

Second is the inprocess quality control. The deployment of latex, the selection of gloves, the make of model, the print on the back of gloves and so on are the inprocess quality control. That means the quality control activities after the storage of materials and before the warehousing of finished goods. And the quality of the testing phase is called final quality control.

Finally is the outgoing quality control. When the goods are finished, the workers will choose the defective goods out. And that will be kept records. The quality record can provide objective evidence about the goods quality.

#### INSTRUCTION FOR USE

#### SHANDONG XINRUIDA LABOR PROTECTIVE PRODUCTS CO., LTD

NORTH OF WEIJIAO ROAD, EAST OF KANGCHENG STREET, ECONOMIC DEVELOPMENT ZONE, GAOMI CITY, SHANDONG

**CHINA** 

Glove reference: Pl

PU134102P

Available sizes:

6/XS 7/S

8/M 9/L

10/XL 11/XXL

#### Glove description:

13G Black Polyester Shell, Black PU Coating Glove

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/686/CEE: innocuousness, comfort, solidity.

It has been subject to a CE type Examination performed by :

C.T.C.

(0075)

4, rue Hermann Frenkel

69367 LYON Cedex 07

**FRANCE** 

#### Applicable standards:

The glove meets the requirements of the standard EN 420 « General requirements for work glove ». Dexterity : 5 Moreover, this glove has been designed for the following applications :



4 1 3 1 X Levels of performance

		4
Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	3	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	Х	(A to F)
Impact Protection		

<sup>«</sup> X » means that the test hasn't been performed; no protection is required

#### Protection limit:

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire.

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

#### Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.