



**DECLARATION OF PERFORMANCE**  
**according to Regulation (EC) 305/2011**  
**№ 1-7-1-CPR-2019**

1.Unique identification code of the product-type:

Area code 27 – roomheaters fired by solid fuel  
EN 13240:2001/A2:2004/AC:2007  
**L101, L102s, L102**

2.Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4):

Serial № (see rating label on the product).

3.Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Freestanding fireplace with hot water supply, for intermittent burning with firedoors closed, intended for room heating.

4.Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11 (5):

**Line Stoves LTD**  
Bld. Kuklensko shose No12, 4004 Plovdiv  
Republic of Bulgaria, E-mail: [info@linestoves.com](mailto:info@linestoves.com)  
Line Stoves

5.Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):

-

6.System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7.In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**Kontrol 94 Ltd.**  
2 Mladost Str., 5100 Gorna Oryahovitsa  
Republic of Bulgaria, Body: NB1879  
Test report: NB 1879-K-06-2019

8.Declared performance:

Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
<b>Fire safety</b>	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm sides=300 rear=350 front=1100
Risk of burning fuel falling out	Pass
<b>Emission of combustion products</b>	CO [0.0773 %] -wood;
<b>Surface temperature</b>	Pass (operating tool)
<b>Electrical safety</b>	NPD
<b>Cleanability</b>	Pass
<b>Maximum water operating pressure</b>	- bar
<b>Flue gas temperature at nominal heat output</b>	T [223°C] -wood;
<b>Mechanical resistance (to carry a chimney/flue)</b>	NPD
<b>Thermal output</b>	
Nominal heat output	7.16 kW -wood;
Room heating output	7.16 kW -wood;
Water heating output	- kW -wood;
<b>Energy efficiency</b>	$\eta$ [83.08%]
<b>Emission of combustion products</b>	dust [25.80 mg/m <sup>3</sup> ] -wood;
	NOx [84.87 mg/m <sup>3</sup> ] -wood;
	CxHy [52.54 mg/m <sup>3</sup> ]

9.The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

10.06.2019  
Plovdiv

Manager: Paris Panagiotidis